


GMS

TELECOMMUNICATIONS/SPECIAL PURPOSE



GMS

- Color Coded
- Body Material PPS UL 94V-0
- Rated 125V AC, 60V DC
- Carry 100% load - 10 minutes, min.
clear 150% load - 5 minutes, max.

GMS SERIES ALARM INDICATING TELECOMMUNICATIONS FUSES

Ferraz Shawmut GMS Series Alarm Indicating fuses are used in telecommunications equipment or other applications. A color coded flag indicates a circuit problem which caused the fuse to blow. Nineteen ampere ratings/colors fill every replacement need.

GMS: Alarm indicating telecommunications fuse

Catalog Numbers, Ampere Ratings, Certifications

AMPERE RATING	CATALOG NUMBER	VOLTS	COLOR CODE
180mA	GMS18/100	125	Yellow
200mA	GMS2/10	125	Black-Red
250mA	GMS1/4	125	Violet
500mA	GMS1/2	125	Red
650mA	GMS65/100	125	Black
750mA	GMS3/4	125	Brown
1A	GMS1	125	Gray
1.33A	GMS1-1/3	125	White
1.5A	GMS1-1/2	125	White-Yellow
2A	GMS2	125	Orange
2.5A	GMS2-1/2	125	White-Orange
3A	GMS3	125	Blue
3.5A	GMS3-1/2	125	White-Blue
4A	GMS4	125	White-Brown
5A	GMS5	125	Green
7.5A	GMS7-1/2	125	Black-White
10A	GMS10	125	Red-White
12A	GMS12	125	Yellow-Green
15A	GMS15	125	Red-Blue

