

REV	DATE	ECO	DESCRIPTION	BY	CHK APP

P/N	WIRE RANGE & TORQUE (IN-LBS)				UL	CSA
	PRIMARY RANGE	TORQUE	SECONDARY RANGE	TORQUE		
66612	2/0-#14	50	#2-#3	50	FILE #	GUIDE #REPORT #
	2/0-#14	45	#4-#6	35		
	#8	40	#2-#14	25	E73571	XCFR2 LR69363
	#10-#14	35	#10-#14	20		
67612	2/0-#14	120	#2-#3	50		
	#8-#14	50	#4-#6	35	E73571	XCFR2 LR15469
			#10-#14	20		

3

3

P/N 66512 USES STD. SLOT DRIVER
P/N 67512 USES 3/16 SOCKET DRIVER

2. (2) 2/0-#14 X (8) #2-#14, 2 POLE, 600V.

1. MATERIAL COMPOSITION AND RATING:
BASE: THERMOPLASTIC 125°C RTI
CONNECTOR: ALUMINUM OR COPPER ALLOY-TIN PLATED

NOTES: UNLESS OTHERWISE SPECIFIED

P/N 66612 (CU ONLY)
67612 (CU-AL)



374 MERRIMAC STREET
NEWBURYPORT, MA 01950

PRODUCT MANAGER

DESIGN ENGINEER

SIGN: *Paul 2th*
DATE: 11-4-96

SIGN: *W. G. Smith*
DATE: 11-4-96

POWER DISTRIBUTION BLOCK

OUTLINE DIMENSIONS
NOT TO BE USED FOR PRODUCTION

700175